D3 MAX

ดี3 แมกซ์ API CF-4/SJ



BCP LUBRICANTS

High Quality Diesel Engine Lubricant

น้ำมันหล่อลื่นเครื่องยนต์ดีเซล

D3 MAX : is the superior lubricating oil for heavy-duty diesel engines equipped with 'turbo-charged or super-charged. It is a multigrade oil which formulated to exceed API CF-4/SJ standard and give superior performance for all heavy-duty engines. The benefits of D3 MAX include extended engine life, outstanding results in high temperature operations, protected engine wear and extended oil drain interval.

ดี3 แมกซ์ : เป็นน้ำมันหล่อลื่นเครื่องยนต์ดีเซล เกรดรวมคุณภาพยอดเยี่ยมสำหรับเครื่องยนต์ดีเซลสมรรถนะสูง งานหนักใช้ได้กับเครื่องยนต์รอบจัดแบบเทอร์โบชาร์จ และแบบธรรมดา ช่วยเพิ่มพลังเครื่องยนต์ ยืดอายุเครื่องยนต์ ทนความร้อนสูง ป้องกันการสึกหรอของแหวน และกระบอกสูบ รักษาความสะอาดเครื่องยนต์ได้ดีเป็นพิเศษ

APPLICATION

- D3 MAX is designed for all heavy-duty diesel engines, truck, bus, tractor, pick up, fishing boat especially high speed diesel engine.
- It can also be used in general gasoline engines and gasoline engines with catalytic converter.

การใช้งานของ ดี3 แมกซ์

- เหมาะสำหรับเครื่องยนต์ดีเซลที่ใช้งานหนักทุกชนิด เช่น รถบรรทุก 10 ล้อ, รถโดยสาร, รถแทรกเตอร์, รถตู้, รถเครน, รถปิคอัพ, เรือประมง
- สามารถใช้ได้กับรถยนต์นั่ง เครื่องยนต์เบนซินทั่วไปทั้งที่ติดเครื่องกรองไอเสีย (CATALYTIC CONVERTER) ได้อีกด้วย

MEET REQUIREMENT / ผ่านการทดสอบมาตรฐานต่างๆ

- API CF-4/SJ

TYPICAL INSPECTION / คุณสมบัติทั่วไปของ ดี3 แมกซ์

PROPERTIES	METHOD	D3 MAX	
		SAE 15W-40	SAE 20W-50
Appearance	Visual	Bright & Clear	Bright & Clear
Color	ASTM D1500	Report	Report
Density @ 15 °C, g/cm^3	ASTM D1298	Report	Report
Flash Point (COC), °C	ASTM D92	215 Min	215 Min
Foam Test (Seq II), ml/ml	ASTM D892	50/0 Max	50/0 Max
Pour Point, °C	ASTM D97	-15 Max	-15 Max
Kinematic Viscosity @ 100 °C, cSt.	ASTM D445	14.5-15.5	18.5-19.5
Viscosity Index	ASTM D2270	120 Min	120 Min
TBN, mg KOH/g	ASTM D2896	8.0 Min	8.0 Min

Packaging / บรรจุภัณฑ์ : 1 Litre / ลิตร และ 6 Litres / ลิตร