Product Data

Castrol Activ Automatic 20W-40

CONTINUOUS PROTECTION

Description

The engine in your bike risks damage all the time, when starting up, when running, and even when the engine is off. New Castrol Activ with Actibond Technology provides 3X Protection: through start-up, while the engine is running, and when the engine is off.

Application

Castrol Activ Automatic 20W-40 is suitable for all 4-Stroke scooter engines where API SN (and below) and/or JASO MB specifications are recommended. Not suitable for motorcycles equipped with wet clutch and passenger cars

Advantages

New Castrol Activ Automatic delivers 3X Protection*

- Provides 50% better wear protection during start-up**
- Fights deposits and provides excellent engine cleanliness during running
- Provides excellent corrosion protection, even when the engine is off

Castrol Activ Automatic contains ACTIBOND TECHNOLOGY TM that offers a protective layer to engine parts.

*Protection in 3 stages of the ride: through engine start-up, running, and while the engine is off.
**Compared to API SN limits in the Sequence IVA wear test.

Typical Characteristics

Name	Method	Units	Castrol Activ Automatic 20W-40
Relative Density @ 15°C	ASTM D4052	g/ml	0.882
Kinematic Viscosity @ 100 °C	ASTM D445	cSt	13.9
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	124
Viscosity Index	ASTM D2270	-	109
Pour Point	ASTM D97	°C	-30
Flash Point, Closed Cup	ASTM D93	°C	220

Performance

API SN
JASO MB

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com