Product Data

POWER1 ULTIMATE Automatic 5W-40

Outstanding Performance

Description

With so many engine oils available in the market, don’t you want to know which one offers uncompromising performance?

The Castrol POWER1 ULTIMATE Automatic 5W-40 fully synthetic range is engineered for outstanding performance across 5 critical areas.

New Castrol POWER1 ULTIMATE Automatic 5W-40's 5-in-1 formula delivers outstanding performance and acceleration.

Application

Castrol POWER1 ULTIMATE Automatic 5W-40 is suitable for all makes of 4-stroke automatic bikes where API SN (or below) and JASO MB specifications are recommended. Strictly not to be used in wet clutch motorcycle engines.

Advantages

- Full Synthetic technology 4-stroke motorcycle engine oil
- Castrol POWER1 ULTIMATE delivers the “POWER of 5” benefits:

1. Excellent acceleration*
2. Excellent protection
3. Smooth riding
4. Keeps the engine cool on long rides
5. Enduring performance

- Complies with requirements of catalyst equipped engines

*Acceleration benefits will be subject to riding style and oil viscosity grade

Typical Characteristics

Name	Method	Units	Castrol POWER1 Ultimate Automatic 5W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.8512
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm²/s	14.29
Viscosity, Kinematic 40C	ASTM D445	mm²/s	88.03
Viscosity Index	ASTM D2270	None	169
Pour Point	ASTM D97	°C	-37

When choosing oil, please refer to your owner's handbook and the product specifications shown below. May also be suitable for other vehicles.

Product Performance Claims

API SN
JASO MB

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com