ENEOS
JAPAN'S No.1 Oil Company
www.eneos.asia

FULLY SYNTHETIC

Prolong Engine Life
Sludge and deposit protection

Product Data Sheet

DESCRIPTION

ENEOS X Series brings the advanced technology and highest quality specification standards together in the premium engine oil especially formulated for the latest generation of cars. The new range in ENEOS product line meets the highest emission norms and fuel saving standards, extend engine lift through reduced sulphur content and helps preventing low-speed pre-ignition (LSPI) events.

ADVANTAGES

ENEOS X SP 5W-40 offers:

- Excellent engine protection at high temperature and RPM.
- Suitable for all high-performance gasoline, including turbocharged vehicles.
- Protect engine for the entire drain interval even under extreme pressure.

PERFORMANCE LEVEL

SP
CF Performance

APPLICABLE

- All types of cars where this viscosity is recommended.
- Suitable for all high-performance gasoline, including turbocharged vehicles.
- Suitable for all types of cars where viscosity is recommended.
- Recommended for cars made by world-leading manufacturers.
- Check user's manual for the manufacturer's recommended oil viscosity grade, API service classification.

CONTAINER SIZE

4 Litre 209 Litre

TYPICAL CHARACTERISTICS

SAE Grade		5W-40
API Performance Grade		SP
Density (15°C) g/cm^3	ASTM D 4052	0.8504
Viscosity mm^2/s (40°C)	ASTM D 445	87.44
(100°C)	ASTM D 445	14.04
Viscosity Index	ASTM D 2270	166
Flash Point °C	ASTM D 6749	240
Pour Point °C	ASTM D 97	-36
Base Number	ASTM D 2896	7.62

Note: Typical characteristics are subject to change without notice (Oct, 2022)

Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations

EASIA
Jul 2023