Product information

PI 25/09/14/2026

Special Tec AA 10W-30 Benzin

Description

Modern premium low-friction motor oil. Thanks to its combination of base oils based on synthetic technology and the latest additives, offers excellent protection against wear, reduces oil and fuel consumption, keeps the engine clean and ensures fast oil penetration of the engine.



Properties

- optimum stability to aging
- smooth engine running
- miscible with all commercially available motor oils
- tested for turbochargers and catalytic converters
- high lubrication reliability
- optimum oil pressure under all operating conditions
- stable against shear forces
- excellent wear resistance
- excellent high and low temperature behavior
- long engine service life
- outstanding engine cleanliness
- instant lubrication after cold start

Specifications / Approvals

API SQ • ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Chrysler MS-6395 • Daihatsu • Fiat 9.55535-CR1 • Ford • GM • GM 6094 M • Honda • Hyundai • Isuzu • Kia • Mazda • Mitsubishi • Nissan • Subaru • Suzuki • Toyota

Technical data

Viscosity SAE class	10W-30 SAE J 300
Density at 15 °C	0,870 g/cm³ DIN 51757
Viscosity at 40 °C	71,0 mm²/s DIN 51562
Viscosity at 100 °C	10,5 mm²/s DIN 51562
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	135 DIN ISO 2909
HTHS at 150°C	< 3,5 mPas ASTM D 5481

Technical data

Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,85 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

Areas of application

Ideal for modern Asian and American gasoline engines with multi-valve technology and turbocharging with and without charge air cooling. Especially suitable where there are long intervals between oil changes and heavy duty engine requirements.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21336 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
4 l Canister plastic	21337 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	21338 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com