Product information

PI 57/09/03/2026

Super Leichtlauf 10W-40



Description

Low-friction motor oil based on synthetic technology. For the high requirements of modern, high-performance gasoline and diesel engines without maintenance interval extension. Saves fuel, provides optimum protection against wear and has a beneficial effect on sealing materials and thus on the leaktightness of engines. Therefore highly suitable for year-round use in vehicles with mileages of over 100,000 km.

Properties

- outstanding engine cleanliness
- tested for turbochargers and catalytic converters
- smooth engine running
- miscible with all commercially available motor oils
- optimum stability to aging
- high shear stability
- instant lubrication after cold start
- high lubrication reliability
- excellent wear protection
- regenerates seals
- especially suitable for vehicles with mileages over 100,000 km
- maintains seals

Specifications / Approvals

ACEA A3 • ACEA B4 • API SP • MB-Approval 229.3 • VW 501 01 • VW 505 00

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Fiat 9.55535-D2 • Fiat 9.55535-G2 • GWM • HAVAL • MB 229.1 • Peugeot Citroen (PSA) B71 2300 • Renault RN 0700 • Renault RN 0710 • Wuling

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,870 g/cm³ DIN 51757
Viscosity at 40 °C	97,0 mm²/s ASTM D7042
Viscosity at 100 °C	14,5 mm²/s ASTM D7042
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	⩽ 7000 mPas ASTM D5293
Viscosity index	155 DIN ISO 2909

Technical data

HTHS at 150°C	⩾ 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	11,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	2,5 DIN ISO 2049

Areas of application

Ideal for vehicles with mileages of over 100,000 km and for modern gasoline, diesel and turbocharged engines.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	9503 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
1 l Canister plastic	21236 AR-DZAR-EN-FR
4 l Canister plastic	9504 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	9505 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	20671 DZAR-EN-FR

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

Super Leichtlauf 10W-40

PI 57/09/03/2026

Available pack sizes

20 l Canister plastic	1304 DE-EN-ES-IT-PT
60 l Black plate barrel	1302 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	1303 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com