Product information
Motorbike 4T Shooter

PI 52/08/18/2026



Description

Optimizes the performance of the engine. Removes deposits in the fuel system, on valves, spark plugs and in the combustion chamber and prevents new deposits. This reduces the fuel consumption. Protects the entire fuel system against corrosion. Prevents carburetor icing. Tested on engines with catalytic converters.

Properties

- increases operational reliability
- good corrosion protection
- tested for the use with catalytic converters
- highly economical
- normalizes gasoline consumption and exhaust emissions
- optimizes engine performance
- environmentally friendly
- for carburetor and fuel-injection engines
- reduces residue

Technical data

Form	liquid
Color / appearance	slightly yellowish
Odor	characteristic
Density at 20 °C	0,804 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

Add to fuel for all 4-stroke engines (aspirated and injection).

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline fuel grades. 80 ml is sufficient for 5 – 10 l of fuel.

Available pack sizes

80 ml Can sheet metal	7822 EN
80 ml Can sheet metal	7829 IT
80 ml Can sheet metal	7837 ES
80 ml Can sheet metal	8292 JA
80 ml Can sheet metal	20557 MXES

Available pack sizes

80 ml Can sheet metal	20587 ID
80 ml Can sheet metal	21371 ZH

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com