Product information

PI 46/08/12/2026

Motorbike Speed Shooter



Description

Modern ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- higher performance gain
- improves acceleration
- prevents carburetor icing
- good corrosion protection
- highly economical
- guarantees optimum combustion
- removes deposits from entire fuel system
- residue-free combustion

Technical data

Base	Additive mixture in carrier fluid
Color / appearance	light brown
Density at 15 °C	0,825 g/cm³
Flash point	>63 °C
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm²/s

Areas of application

For 2-stroke and 4-stroke gasoline engines (carburetor and injection).

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline fuel grades. 80 ml is sufficient for up to 10 l of fuel.

Available pack sizes

80 ml Can sheet metal	7820 EN
80 ml Can sheet metal	8265 JA

Available pack sizes

80 ml Can sheet metal	20585 ID

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com