Product information
Motorbike T410 10W-40

PI 5/11/26/2025

Description
High-performance motor oil for 4-stroke engines with a dry clutch and separately lubricated transmission. Enables maximum performance and outstanding engine protection under all operating conditions. Ensures reliable lubrication, optimal noise damping, and minimal wear. The JASO MB specification denotes a particularly friction-reducing property.



Properties
- optimum stability to aging
- guarantees low oil consumption
- optimum lubrication under all operating conditions
- tested for the use with catalytic converters
- friction and wear reducing
- ensures maximum engine performance

Specifications
API SP • JASO MB

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,860 g/cm³ ASTM D4052
Viscosity at 40 °C	95,0 mm²/s ASTM D445
Viscosity at 100 °C	14,1 mm²/s ASTM D445
Viscosity at -30 °C (MRV)	⩽ 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	⩽ 7000 mPas ASTM D5293
Viscosity index	150 ASTM D2270
HTHS at 150°C	⩾ 3,7 mPas ASTM D5481
Pour point	-42 °C ASTM D97
Evaporation loss (Noack)	% ASTM D5800
Flash point	230 °C ASTM D92
Total base number	7,1 mg KOH/g ASTM D2896
Sulfate ash	g/100g ASTM D872
Color number (ASTM)	2,0 ASTM D1500
Oil base	Advanced Full Synthetic

Areas of application
For air and water-cooled 4-stroke engines exposed to normal to difficult operating conditions.

Application
Note the vehicle and engine manufacturers' operating instructions. Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	48332 EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com