Product information

PI 46/08/18/2026

Motorbike 4T Bike-Additive



Description

Optimizes the performance of the engine. Removes deposits in the fuel system, on valves, spark plugs and in the combustion chamber and prevents new deposits. This reduces the fuel consumption. Protects the entire fuel system against corrosion. Prevents carburetor icing. Tested on engines with catalytic converters.

Properties

- increases operational reliability
- highly economical
- environmentally friendly
- optimizes engine performance
- tested for the use with catalytic converters
- reduces the risk of knocking combustion
- normalizes gasoline consumption and exhaust emissions
- for carburetor and fuel-injection engines
- reduces residue
- prevents corrosion in the fuel system

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,806 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application

Add to fuel for all 4-stroke engines (aspirated and injection).

Application

125 ml formulated for 15 – 20 l of fuel. Add every time you refuel.

Available pack sizes

125 ml Can sheet metal	1581 DE-EN
125 ml Can sheet metal	5918 DE-FR-IT-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com