Product information
Speed Petrol Additive

PI 35/09/09/2026



Description
Ash-free, self-mixing combination of active agents. Characterized by its outstanding cleaning and material protection properties.

Properties
- good corrosion protection
- increases operational reliability
- tested for turbochargers and catalytic converters
- reduces the risk of knocking combustion
- for carburetor and fuel-injection engines
- reduces residue
- prevents the build-up of deposits
- keeps the fuel system clean

Technical data

Form	liquid
Color / appearance	yellow
Odor	characteristic
Density at 20 °C	0,813 g/ml
Flash point	>61 °C
Shelf life in original sealed container	60 months

Areas of application
For all 2-stroke and 4-stroke gasoline engines in the automotive sector as well as the shipping and industrial sector. Also suitable for the preservation of engines during long periods of non-use.

Application
Contents (1 l) sufficient for 400 l of gasoline. One measuring cup (25 ml integrated in the cap) is sufficient for 10 l of fuel. The product mixes with the fuel automatically. For long-term application with every refueling.

Available pack sizes

1 l Can sheet metal	5105 DE
195 l Black plate barrel	4054 EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com