Product information

PI 44/08/18/2026

Motorbike Gasoline Stabilizer



Description

Preserves and protects fuel against aging and oxidation. Prevents corrosion throughout the entire fuel system. Prevents problems from occurring when motorbikes, motor scooters, ATVs, snowmobiles and other gasoline-driven 4-stroke and 2-stroke engines are decommissioned. Increases operational reliability. The product has a long-term effect.

Properties

- tested for the use with catalytic converters
- has a lasting effect
- protects fuel against oxidation and aging
- increases operational reliability
- simple to use
- cost-effective due to exact dosage

Technical data

Base	additive mixture in carrier liquid
Color / appearance	blue
Odor	characteristic
Form	liquid
Density at 15 °C	0,822 g/cm³
Hazard class as per German VbF	A III
Flash point	>61 °C
Viscosity at 40 °C	<7 mm²/s

Areas of application

Suitable for all 4-stroke and 2-stroke gasoline engines – especially for preventive care. Tested for turbochargers and catalytic converters.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application

Add to the fuel and repeat dosage after refueling. Filling the dosage chamber (25 ml) once is sufficient for 5 l of fuel. Also suitable for long-term use in seldom used engines. Before putting into storage, add the appropriate amount to the tank and run the engine for approx. 10 minutes.

Available pack sizes

250 ml Dispensing bottle plastic	3041 DE-EN-ES-PT

Available pack sizes

250 ml Dispensing bottle plastic	5921 DE-FR-IT-NL

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com