Product information
Oil Smoke Stop

PI 22/10/09/2026



Description
Reduces the oil consumption of gasoline and diesel engines via the piston rings and valve guides. It prevents blue smoke and oil mist and acts against the loss in viscosity in motor oil. Improves the sealing and reduces engine noise. Provides extra protection in engines with high levels of wear. Extends the service life of catalytic converters.

Properties
- reduces oil consumption
- high shear stability
- stabilizes loss of viscosity

Technical data

Color / appearance	yellow, clear
Appearance / properties	viscous liquid
Density at 20 °C	0,851 g/ml
Viscosity at 40 °C	183 mm²/s
Flash point	120 °C
Odor	characteristic
Form	liquid

Areas of application
For all types of gasoline and diesel engines.
Compatible with all commercially available motor oils.
Not suitable for use in motorbikes with wet clutches.

Application
One 300 ml can is sufficient for 4 – 6 l of motor oil. Do not add more than 10%. Add to the warm motor oil during every oil change and between oil changes if oil consumption is very high.

Available pack sizes

300 ml Can sheet metal	2122 DE-ES-PT
300 ml Can sheet metal	2808 DA-FI-NO-SV
300 ml Can sheet metal	8360 AR-EN-FR
300 ml Can sheet metal	8901 EL-EN-IT
300 ml Can sheet metal	20800 DE-EN-HR-SL-SR
300 ml Can sheet metal	20874 JA
300 ml Can sheet metal	21308 AR-DZAR-EN-FR

Available pack sizes

300 ml Can sheet metal	21351 DE-EN-ZH

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com