Product information
Injection Cleaner

PI 38/09/09/2026



Description
Removes deposits on injection valves, intake valves, spark plugs and in the combustion chamber and prevents new deposits from forming. Eliminates starting problems and rough engine running. Maintains all components of the gasoline injection system. Protects the entire fuel system against corrosion. Improves throttle response and compression. Optimizes the emission test values and the performance of the engine. Clean engines use less fuel and reduce the pollutant emissions.

Properties
- tested for turbochargers and catalytic converters
- cost-effective due to exact dosage
- removes carbon deposits from intake valves and combustion chamber
- cleans the injection system

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	> 61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm²/s
Density at 15 °C	0,7989 g/ml

Areas of application
For all gasoline engines, gasolines and operating conditions. Suitable for all gasoline injection systems, both direct and manifold fuel injection systems and combined systems. Preventive or remedial. To be added directly into the fuel tank. Tested for turbochargers and catalytic converters.

Application
300 ml is sufficient for 70 l of fuel. Has a long-term effect of 2,000 km. Can be mixed with fuel at any time since mixing takes place automatically. Repeat treatment if problems reoccur.

Available pack sizes

300 ml Can sheet metal	1803 EL-EN-IT
300 ml Can sheet metal	1971 BG-DE-PL

Available pack sizes

300 ml Can sheet metal	2124 DE-EN-ES
300 ml Can sheet metal	2522 DE-ES-PT
300 ml Can sheet metal	2786 AUEN-EN
300 ml Can sheet metal	2822 DA-FI-NO-SV
300 ml Can sheet metal	2902 EN-HE
300 ml Can sheet metal	5110 DE-FR-NL
300 ml Can sheet metal	7128 AR-DZAR-EN-FR
300 ml Can sheet metal	8361 AR-EN-FR
300 ml Can sheet metal	8376 DE-HU-RO
300 ml Can sheet metal	20804 DE-EN-HR-SL-SR
300 ml Can sheet metal	20867 JA
300 ml Can sheet metal	21502 DE-FR
300 ml Can sheet metal	21990 MXES
50 l Black plate barrel	5113 DE-EN
195 l Black plate barrel	4036 DE-EN
1.000 l Container	21909 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com