Product information

PI 28/08/07/2026

Pro-Line Automatic Transmission Cleaner



Description

Highly effective cleaning fluid designed to dissolve problematic deposits and residues in automatic transmissions for optimum shifting performance, thus extending the transmission service life. These highly effective detergent and dispersant additives in association with the carrier fluid have been tested in the laboratory and in practical field trials for their ability to dissolve sludge and lacquer formers.

Properties

- gentle cleaning
- does not attack rubber and plastic seals
- assures optimum shifting performance
- optimizes economical use
- easily dissolves stubborn dirt

Technical data

Base	additive, naphtha-base special oil
Viscosity index	204
Viscosity at 40 °C	58 mm²/s
Viscosity at 100 °C	11,8 mm²/s
Form	flüssig, liquid
Odor	characteristic
Density at 15 °C	0,885 g/ml

Areas of application

Suitable for all automatic transmissions and power steering systems without an additional system. 300 ml are sufficient for 6-9 l of ATF.

Comment

For all automatic transmissions. Also for CVT and DSG transmissions.

Application

Add the appropriate amount of the can contents to the gear oil and then run the engine for 10 – 15 minutes at idle speed. Shift through all gears once or twice. Then stop the engine and change the oil and the oil filter. For optimum effect we recommend the use of our automatic transmission service device Gear Tronic.

Available pack sizes

1 l Can sheet metal	5101 DE-EN-ES-IT-PT

Available pack sizes

5 l Canister plastic	5179 DE-EN-ES-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com