Product information
ATF Additive

PI 32/08/18/2026



Description
The additives contained provide optimal care of rubber and plastic seals in the steering gear and automatic transmission. Leaks on transmissions caused by hardened or brittle seals are prevented or remedied. Holes and ducts in the gears are also cleaned, and the performance of the oil is revitalized. The noise generation of power steering systems is reduced and the shifting operations of automatic transmissions are improved. Can extend the service life of steering gears and automatic transmissions and lower the repair costs.

Properties
- high wear resistance
- prevents oil loss
- minimizes unwanted noise
- cleans and maintains
- regenerates seals
- prevents rapid aging of oil
- increases service life
- stable to oxidation
- care and protection
- prevents expensive repairs
- damps shifting operations

Technical data

Color / appearance	brown
Viscosity at 40 °C	~ 166 mm²/s DIN 51562
Viscosity at 100 °C	~ 26 mm²/s DIN 51562
Density	0,888 g/ml
Refractive index at 20 °C	~ 1,478
Form	liquid
Odor	characteristic

Areas of application
Suitable for all steering gears and automatic transmissions that are filled with ATF II and ATF III oils.

Application
Mix additive into the gear oil using the dipstick. Contents (250 ml) sufficient to treat up to 8 liters of oil.

Available pack sizes

250 ml Tube plastic	2702 AUEN-EN
250 ml Tube plastic	5135 DE-EN-ES-IT-PT

Available pack sizes

250 ml Tube plastic	8336 AR-EN-FR

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com