Product information

PI 32/08/18/2026

Power Steering Oil Leak Stop



Description

Due to the additives contained, rubber and plastic seals in steering gears receive optimal care. Leaks on transmissions caused by hardened or brittle seals are prevented or remedied. Holes and ducts in the gears are also cleaned and the performance of the oil is revitalized. The noise levels of power steering systems are reduced. The service life of the steering gears can be extended and the repair costs reduced.

Properties

- good corrosion protection
- prevents oil loss
- minimizes unwanted noise
- cleans and maintains
- regenerates seals
- prevents rapid aging of oil
- increases service life

Technical data

Color / appearance	brown
Viscosity at 40 °C	~ 166 mm²/s DIN 51562
Viscosity at 100 °C	~ 26 mm²/s DIN 51562
Density	0,888 g/ml
Refractive index at 20 °C	~ 1,478
Form	liquid
Odor	characteristic

Areas of application

Suitable for steering gears that are filled with ATF II, ATF III, ATF VI or central hydraulic system oils.

Application

Add to the compensating reservoir of the steering system. 35 ml are sufficient for 1 l of oil.

Available pack sizes

35 ml Tube plastic	1099 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com