Product information
Air Flow Sensor Cleaner

PI 23/09/02/2026



Description
Special active solvent for fast and gentle cleaning of sensitive components of the air flow sensor in gasoline and diesel engines. The Cleaner also distinguishes itself by means of a very fast evaporation that is free of residues. A dirty hot wire or hot plate in the air flow sensor leads to incorrect readings for calculating the fuel/air mixture. The starting and idling properties of the vehicle are thus impaired, the engine performance is reduced and the fuel consumption increases. Also, dirty sensors on vehicles with automatic transmissions can cause shifting problems. Thanks to the use of the Air Flow Sensor Cleaner, an expensive replacement of the sensor can most likely be avoided.

Properties
- economical
- simple to use
- fast evaporation free of residues
- excellent cleaning effect

Technical data

Form	liquid, aerosol
Base	mixture of solvent
Color / appearance	colourless
Odor	characteristic
Propellant	CO2

Areas of application
Removes contaminants from the hot wire or hot plate of air flow sensors. Suitable for use in gasoline and diesel engines.

Application
Disconnect electrical connection of the air flow sensor and remove the sensor. Spray generously onto dirty components such as the hot wire or hot plate and allow the dirt to drip off. Do not touch the sensitive components of the sensor. Allow the solvent to dry completely before installation. Application is recommended every time the air filter is replaced or when problems arise.
Note: Before using on plastics that are sensitive to solvents, especially on mechanically-loaded parts, test for compatibility.

Available pack sizes

158 g Can aerosol	7085 AUEN-EN
200 ml Can aerosol	4066 DE-EN-PT

Available pack sizes

200 ml Can aerosol	21703 HU-PL-RO

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com