Product information

PI 15/03/25/2026

Pro-Line Turbocharger Additive



Description

Used for the initial filling of new turbochargers in order to protect them against dry running and damage caused by lack of oil after changing to the running-in phase. Improves the operational reliability of the new turbocharger.

Properties

- miscible with all commercially available motor oils
- increases operational reliability
- outstanding emergency-running properties
- protects against damage caused by lack of oil in the running-in phase

Technical data

Color / appearance	dark grey - black
Solids content	~ 10 %
Viscosity at 20 °C	304,31 mPas DIN 51398
Flash point	> 100 °C DIN ISO 2592
Pour point	-15 °C DIN ISO 3016
Thermal stability	> 400 °C
Form	liquid
Odor	chracteristic
Density at 20 °C	1,0013 g/cm³

Areas of application

Suitable for all turbochargers. Can be blended with all motor oils.

Application

The oil intake passage of the turbocharger is filled to the brim with Pro-Line Turbocharger Additive before the oil supply line is connected.

Available pack sizes

20 g Tube plastic	20766 DE
20 g Tube plastic	21651 EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com