Product information

PI 15/09/02/2026

Pro-Line JetClean Gasoline Intake System Cleaner



Description

Highly effective additive combination for direct use with the JetClean Tronic II. Removes typical contamination and deposits in the intake and throttle valve area. Loosens and removes all greasy contamination such as oil, resin, adhesive, etc. Ensures the operability of all moving parts and reduces fuel consumption. Increases the operational reliability of gasoline-powered engines.

Properties

- tested for turbochargers and catalytic converters
- simple to use
- rapid cleaning
- excellent cleaning effect
- cleaning possible without dismantling
- ready for use

Technical data

Form	liquid
Viscosity at 40 °C	<7 mm²/s
Odor	characteristic
Density at 15 °C	0,894 g/cm³
Flash point	-18 °C
Color / appearance	light yellow

Areas of application

For the intake and throttle valve area. Only for use in gasoline engines!

Application

Ready for use for undiluted filling of the JetClean Tronic II. A detailed description of further application is given in the instructions of the JetClean Tronic II.

Available pack sizes

300 ml Can sheet metal	20985 DE-EN-ES

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com