# Product information

PI 22/08/18/2026

# Pro-Line Injector and Glow Plug Grease



## Description

Partly synthetic, metal-free special grease for lubricating injectors and spark and glow plugs before installation in the engine. Blocks the ingress of moisture and so prevents corrosion of the injector and glow plug. The special grease also makes disassembly much easier.

## Properties

- highest load-carrying capacity
- excellent corrosion protection
- prevents seizing and cold welding
- does not attack common sealing materials
- resistant to certain organic acids and alkalis
- especially resistant to cold and hot water

## Technical data

| | |
|---|---|
| Color / appearance | weiß/white |
| Density at 20 °C | 1,09 g/cm³ |
| Form | paste |
| Thickener | inorganic thickeners and light solid lubricants |
| Dropping point | no one |
| Operating temperature range | -40 to 1400 °C |
| Base | synthetic oil, mineral oil |
| Base oil viscosity 40°C | 100 mm²/s |

## Areas of application

For the lubrication of all kinds of high-load sliding surfaces and separating components subject to heat stress such as injectors, spark and glow plugs, pins and bolts.

## Application

Before being treated with the special grease, all components must be clean and free of residues, dirt and moisture. Apply to the cleaned surfaces using a paint brush, brush or lint-free cloth. Apply the amount which is appropriate for the application.

## Available pack sizes

| | |
|---|---|
| 20 g Tube plastic | 3381 |
| | DE-EN |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com