Product information
Central Hydraulic System Oil

PI 64/08/18/2026



Description
LIQUI MOLY central hydraulic system oils meet the highest technical requirements and are suitable for a wide range of automotive applications. The carefully selected formulations made from the best raw materials ensure excellent temperature properties and guarantee the full function of the systems even at the lowest temperatures of up to –45 °C. All central hydraulic system oils are impressive thanks to excellent wear, aging and corrosion protection as well as optimum friction values and minimal foaming tendency.

Properties
- optimum stability to aging
- excellent low temperature behavior
- excellent viscosity/temperature properties
- highest thermal stability
- outstanding corrosion protection

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:
BMW 81 22 9 407 758 • DTFR 31B120 • Fiat 9.55550-AG3 • Ford WSS-M2C 204-A • MAN M 3289 • MB 345.0 • MB 345.1 • Opel 1940 766 • VW G 002 000 • VW G 004 000 • ZF TE-ML 02K

Technical data

Viscosity at 40 °C	19,5 mm²/s ASTM D 7042-04
Viscosity at 100 °C	6,1 mm²/s ASTM D 7042-04
Viscosity index	300 DIN ISO 2909
Color / appearance	green
Density at 15 °C	0,825 g/cm³ DIN 51757
Flash point	150 °C DIN ISO 2592
Pour point	-51 °C DIN ISO 3016
Foaming behavior at 24 °C	50/0 ml ISO 6247
Foaming behavior at 93.5 °C	35/0 ml ISO 6247

Areas of application
This synthetic hydraulic fluid with ash-free additives is ideally suited for steering systems, electro-hydraulic convertible tops, level controls, hydropneumatic suspensions, damping systems, cab tilting devices, etc.

⚠ WARNING: This product can expose you to chemicals including naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Application
Shake well before use. The specifications and instructions from the assembly or vehicle manufacturer must be followed. This oil can also be used for refilling in systems. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Can plastic	1127 DE-EN-ES-IT-PT
1 l Can plastic	1158 AR-DE-EL-FR-NL
1 l Can plastic	2366 DA-EN-FI-NO-SV
1 l Can plastic	9524 AR-DE-EN-FR
1 l Can plastic	20468 CS-HU-PL-RO-SK-TR
1 l Can plastic	21239 AR-DZAR-EN-FR
20 l Canister plastic	1147 DE-EN-ES-IT-PT
60 l Black plate barrel	1148 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com