Product information

PI 43/08/17/2026

Coolant & Antifreeze Ready Mix RAF 11



Description

Premixed product based on ethylene glycol. Antifreeze that does not contain amines, nitrites or phosphates and offers outstanding protection against frost, corrosion and overheating thanks to its special inhibitor package. Enables safe, year-round vehicle operation.

Properties

- outstanding corrosion protection
- prevents the cooling system from freezing up
- prevents operational malfunctions
- contains no amines, nitrites or phosphates
- ready for use
- provides outstanding protection against overheating
- for extended change intervals (note manufacturer's instructions)

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Alfa Romeo 9.55523 • Behr • BMW GS 94000 • Chrysler MS-7170 • Cummins 85T8-2 • Deutz DQC CA-14 • Fiat 9.55523 • IVECO 18-1830 • JI Case JIC-501 • Lada/Avtovaz TTM VAZ 1.97.717-97 • Lancia 9.55523 • MTU MTL 5048 • Opel/GM GME L 46014 • Perkins • Saturn • Toyota Motor Corporation • Vauxhall GMEL1301 • Volvo Cars 128 6083 / 002 • Volvo Construction • Volvo Trucks

Technical data

Color / appearance	bluegreen
Odor	characteristic
Flash point	> 125 °C
Density at 20 °C	1,06 g/cm³
Base	Ready Mix (50:50)
Frost protection	up to - 40°C

Areas of application

For all cooling systems and engines (including aluminum engines) in cars, commercial vehicles, buses, agricultural machinery as well as stationary engines and equipment that require cooling system protection of this quality.

⚠ 0

Application

Clean cooling system with Radiator Cleaner (part no. 3320). Then drain the cooling system, flush it thoroughly with water and fill with Coolant & Antifreeze Ready Mix RAF 11. Disposal according to the local regulations. Change interval according to manufacturer's instructions. Coolant & Antifreeze Ready Mix RAF 11 is miscible and compatible with radiator antifreeze containing silicates with quality VW designation G11, VW specification TL 774-C (LIQUI MOLY Coolant & Antifreeze KFS 11) or with silicate-free radiator antifreeze from the original products in accordance with the VW specification TL 774-D/F (LIQUI MOLY Coolant & Antifreeze KFS 12+ or Coolant & Antifreeze Ready Mix RAF 12+).

Available pack sizes

1 l Canister plastic	20660 DE-EN
5 l Canister plastic	8809 DE-EN-ES-IT-PT
20 l Canister plastic	8822 DE-EN-ES-IT-PT
200 l Black plate barrel	8823 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com