Shell **Helix City** *5W-30*

Fully Synthetic Passenger Car Motor Oil

Shell Helix City is designed for drivers to protect engines running efficiently in demanding driving conditions and in busy traffic with start-stop mode.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- Everyday motorway or city driving can mean severe conditions for engine oil. Shell Helix City helps to extend engine life by protecting against wear in demanding daily traffic conditions.

Main Applications

- Shell Helix City motor oil is enhanced with Seals Conditioning Technology to help to rejuvenate seals and prevents leaks and protects the engine.

Specifications, Approvals & Recommendations

- API SP
- ILSAC GF-6A

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representatives or technical helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Helix City 5W-30
Density	@15°C	kg/m³	ASTM D4052	837
Kinematic Viscosity	@100°C	cSt	ASTM D445	10.8
Kinematic Viscosity	@40°C	cSt	ASTM D445	60.7
Flash Point		°C	ASTM D92	212
Pour Point		°C	ASTM D97	-48

These characteristics are typical of current production, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shell representative.

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

  Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Helpdesk.