Shell **Helix** *ECO 0W-20*

Fully Synthetic Motor Oil -Relentless performance, cleansing and protection

Shell Helix ECO 0W-20 is designed particularly for Low Cost Green Cars (LCGC) to offer a high level of protection and cleansing for the modern gasoline engines. It also helps to reduce engine friction to provide enhanced fuel economy.

Proud Drivers Choose Shell Helix

Main Applications

Shell Helix ECO 0W-20 for gasoline engines is approved against the technically challenging API SN and ILSAC GF-5 specifications.

Specifications, Approvals & Recommendations

- API SN
- ILSAC GF-5

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix ECO 0W-20
Kinematic Viscosity	@100°C	cSt	ASTM D445	8.59
Kinematic Viscosity	@40°C	cSt	ASTM D445	46.75
Viscosity Index			ASTM D2270	164
MRV	@-40°C	cP	ASTM D4684	17 700
Density	@15°C	kg/m^3	ASTM D4052	836.1
Flash Point		°C	ASTM D92	243
Pour Point		°C	ASTM D97	-54

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  Shell Helix ECO 0W-20 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from http://www.epc.shell.com/

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.