Shell **Helix** *Eco Plus 0W-30*

WITH Shell PUREPLUS TECHNOLOGY

A Fully Synthetic Motor oil that provides enhanced fuel economy

Proud Drivers Choose Shell Helix

Main Applications

- Shell Helix Eco Plus works hard to help keep modern engines clean and protected. It helps to prevent the formation of harmful deposits that can lead to performance loss and helps to reduce engine friction to provide enhanced fuel economy and lower emissions.
- Shell Helix Eco Plus can be used for gasoline engines, diesel engines (without particulate filters) and gas engines, and it is also suitable for use with biodiesel and gasoline/ethanol blends.

Specifications, Approvals & Recommendations

- API SP
- ACEA A3/B4

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix Eco Plus 0W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	11.8
Kinematic Viscosity	@40°C	cSt	ASTM D445	61
Viscosity Index			ASTM D2270	193
MRV	@-40°C	cP	ASTM D4684	19 000
Density	@15°C	kg/m^3	ASTM D2270	838
Flash Point		°C	ASTM D92	217
Pour Point		°C	ASTM D97	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from https://www.epc.shell.com

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.