Shell **Helix** *HX5 Diesel 10W-30*

Premium multi-grade motor oil - Helps to remove sludge from dirty engines

Shell Helix HX5 Diesel is designed to provide consistent light-duty diesel engine performance. It works hard to help protect against harmful soot deposits and wear by helping to control the oil thickness.

Proud Drivers Choose Shell Helix

Main Applications

- Shell Helix HX5 Diesel's premium multigrade formulation helps to provide protection in everyday daily driving conditions. Shell Helix HX5 Diesel can be used for passenger car diesel engines requiring API CI-4, CH-4 and earlier specifications and it is also suitable for biodiesel.

Specifications, Approvals & Recommendations

- API CI-4, CH-4, CG-4

  To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com

  Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks

Typical Physical Characteristics

Properties			Method	Shell Helix HX5 Diesel 10W-30
Kinematic Viscosity	@100ºC	cSt	ASTM D445	12.0
Kinematic Viscosity	@40ºC	mm^2/s	ASTM D445	79.78
Viscosity Index			ASTM D2270	145
Density	@15ºC	kg/m^3	ASTM D4052	870.0
Flash Point		ºC	ASTM D92	228
Pour Point		ºC	ASTM D97	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from https://www.epc.shell.com/

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.