Technical Data Sheet

Shell **Advance Fuel Save** *10W-30 SP/MB*

Expertly engineered to improve Fuel economy and Reduce friction.

DESIGNED TO MEET CHALLENGES

Specifications, Approvals & Recommendations

- API SP
- JASO MB

For a full listing of equipment approvals and recommendations, please consult your local representative.

Typical Physical Characteristics

Properties			Method	Shell Advance Fuel Save 10W-30 SP/MB
Kinematic Viscosity	@100°C	cSt	ASTM D445	10.3
Kinematic Viscosity	@40°C	cSt	ASTM D445	63.7
Pour Point		°C	ASTM D97	-33
Flash Point		°C	ASTM D92	269
Density	@15°C	kg/m^3	ASTM D4052	839
Colour			Visual	Amber
State of Matter				Liquid
Form				Liquid at room temperature.

These characteristics are typical of current production.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet.

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.