Technical Data Sheet

Shell **Advance City** *10W-40 (SP/MA2)*

Fully-Synthetic Motorcycle Engine Oil

DESIGNED TO MEET CHALLENGES

Specifications, Approvals & Recommendations

- API SP
- JASO MA2

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Advance City 10W-40 (SP/MA2)
Kinematic Viscosity	@100°C	mm^2/s	ASTM D445	14.02
Kinematic Viscosity	@40°C	mm^2/s	ASTM D445	89.58
Pour Point		°C	ASTM D97	-33
Flash Point		°C	ASTM D92	267
Density	@15°C	kg/m^3	ASTM D4052	839
Colour			Visual	amber
Form				Liquid
State of Matter				Liquid

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet.

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.