Technical Data Sheet

Shell Advance Power 15W-50 (SP/MA2)

WITH Shell PUREPLUS TECHNOLOGY

Fully Synthetic 4-Stroke Motorcycle Engine Oil

Shell Advance Power with PurePlus Technology gives your engine long-lasting power and responsiveness.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Retains output power at different speeds
- Enhance responsiveness

Specifications, Approvals & Recommendations

- API SP
- JASO MA2

For a full listing of approvals and recommendations, please consult your local Technical Helpdesk

Typical Physical Characteristics

Properties			Method	Shell Advance Power 15W-50 SP/MA2
Kinematic Viscosity	@100°C	cSt	ASTM D445	20.68
Kinematic Viscosity	@40°C	cSt	ASTM D445	148.54
Pour Point		°C	ASTM D97	-30
Flash Point		°C	ASTM D92	267
Density	@15°C	kg/m^3	ASTM D4052	845
Colour			Visual	Amber
Form				Liquid
State of Matter				Liquid

These characteristics are typical of current production, variations in these characteristics in future production may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet.

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.