Shell Advance *4T Ultra 10W-40 SP MA2*

DESIGNED TO MEET CHALLENGES

Specifications, Approvals & Recommendations

- API SP
- JASO MA2

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Advance 4T Ultra 10W-40 SP MA2
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.02
Kinematic Viscosity	@40°C	cSt	ASTM D445	89.58
Density	@15°C	kg/m³	ASTM D4052	839
Pour Point		°C	ASTM D97	-33
Flash Point		°C	ASTM D92	267
Colour			Visual	amber
State of Matter				Liquid
Form				Liquid

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from https://www.epc.shell.com

- **Protect the Environment**

  Take used oil to an authorised collection point. Do not discharge into drains, soil or water.