Technical Data Sheet

Shell **Advance** *Scooter Gear Oil*

Shell Advance Scooter Gear Oil is suitable for automatic gear boxes of major scooter makes & models. It is specially formulated for scooter gear box for smooth transmission and wear protection.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Easy & no-mess top up of gear oil with funnel spout bottle design
- For best result, use with Shell Advance scooter lubricant

Main Applications

- Ideal for lubrication of automatic gear boxes of major scooter makes & models.

Specifications, Approvals & Recommendations

- API SG
- SAE 15W-40
- Suitable for use in all scooter gearbox

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Advance Scooter Gear Oil
SAE grade				15W-40
Kinematic Viscosity	@40°C	cSt	ASTM D445	104.1
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.4
Viscosity Index			ASTM D2270	142
Density	@15°C	kg/m^3	ASTM D4052	883
Flash Point		°C	ASTM D92	236
Pour Point		°C	ASTM D97	-9

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

Health and Safety

Shell Advance Scooter Gear Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from http://www.epc.shell.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

Advice

Advice on applications not covered here may be obtained from your Shell representative.