Hi-Perf 4T 500 Scooter 10W-30

4-Stroke Engine Oil

KEY DATA



Premium mineral engine oil

INTERNATIONAL STANDARDS

- JASO MB - M033TEL007
- API SL

TECHNOLOGIES

Durability Improver technology

4 Actions to maximize the durability of your bike:

- Protection against harmful piston deposits
- Protection against gear pitting and wear
- Protection against clutch slippage
- Protection against thermo-oxidative attack

APPLICATIONS

Hi-Perf 4T 500 Scooter 10W-30 is a premium 4-stroke engine oil Specially designed for Scooters and gearless 2-wheelers. Formulated with Durability Improver technology, it is Specially designed to reduce friction and provide superior protection against oxidation and deposits, which results in enhanced cleanliness of your engine.

PERFORMANCES & CUSTOMER BENEFITS

- • Reliable city commuting performance: Designed for daily start-stop scooter use, minimizing wear during frequent acceleration and deceleration.
- • Enhanced cleanliness: Effectively reduces piston and valve deposits, keeping the engine running smoother for longer.
- • Improved transmission feel: Promotes quieter, more responsive transmission in gearless scooter systems.
- • Optimized formulation for durability: Maintains viscosity and protective film even in extended drain intervals.
- • Balanced protection: Ideal blend of economy and engine care for everyday scooter riders.

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	10W-30
Kinematic viscosity at 40°C	mm^2/s	ASTM D445	71.6
Kinematic viscosity at 100°C	mm^2/s	ASTM D445	10.7
Flash Point	°C	ASTM D92	236
Viscosity index	-	ASTM D2270	138
Pour point	°C	ASTM D97	-39
Density	kg/m^3	ASTM D1298	866.9

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at https://ms-sds.totalenergies.com.

This product should not be used for any purposes other than the ones for which it is intended.

TotalEnergies

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.