

VALVOLINE DURABLEND MOTOR OIL

DURABLEND SAE 5W-30 and 10W-40 are multi-grade motor oils formulated with advanced additive technology and premium-quality synthetic and highly refined base oils that protect modern engines against undesirable deposits, contamination, and thermal breakdown under severe service conditions.

DURABLEND SAE 5W-30 and 10W-40 are designed to meet the performance requirements of virtually all naturally aspirated, turbocharged, and supercharged passenger cars.

Advantages:

- Delivers very good protection for turbocharged gasoline Direct Injection engines from Low-Speed Pre-Ignition (LSPI) and timing chain wear
- Resists breakdown in the most severe engine environments
- Flows easily at low temperatures for enhanced cold start protection
- Fights the formation of sludge and varnish deposits that reduce engine life
- Contains anti-wear additives that dramatically reduce engine wear
- Provides very good engine cleanliness through superior sludge and varnish protection

PERFORMANCE LEVEL
API SP
ILSAC GF-6A (SAE 5W-30)

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specifications, variations in these characteristics may occur.

Typical Characteristics		
SAE Viscosity Grade	**5W-30**	**10W-40**
Kinematic Viscosity, cSt @ 100ºC	10.43	14.63
Viscosity Index	157	154
TBN, mg KOH/g	7.2	7.2
Pour Point, ºC	-36	-36
Flash Point, COC, ºC	230	236
CCS, cP @ -30 ºC CCS, cP @ -25 ºC	6319 -	- 6149

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local sales representative or through our website https://sds.valvoline.com .

This information only applies to products manufactured in the following location(s): Thailand

Product Code:
5W-30 : 100061 100076
10W-40 : 100010 100011 100013

Effective Date
June 3, 2025

Author
CR

™ Trademark, Valvoline Global Operations