

VALVOLINE MAXLIFE™ MOTOR OIL

Valvoline Maxlife™ SAE 10W-40 is the first motor oil specially formulated to address the unique needs of higher mileage engines. **Valvoline Maxlife™** is a blend of synthetic and premium conventional base stocks with seal conditioning agents, extra cleaning agents, additional anti-wear additives, and novel friction modifiers for added protection. **Valvoline Maxlife™** provides performance benefits for high mileage, new, and re-built engines.

It is specifically formulated to:

- Condition seals
- Reduce oil consumption
- Reduce friction
- Resist thermal breakdown

Valvoline Maxlife™ is suitable for use in both new and re-built engines.

PERFORMANCE LEVEL
API SP

Typical properties:
Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specifications, variations in these characteristics may occur.

Typical Characteristics	
SAE Viscosity Grade	**10W-40**
Kinematic Viscosity, cSt @ 100ºC	14.79
Viscosity Index	152
TBN, mg KOH/g	7.0
Pour Point, ºC	-33
Flash Point, COC, ºC	236
CCS, cP @ -25 ºC	6875

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local sales representative or through our website https://sds.valvoline.com .

This information only applies to products manufactured in the following location(s): Thailand

Product Code:	**Effective Date**	**Author**
10W-40 : 100015 100043 100065	July 2, 2025	CR

™ Trademark, Valvoline Global Operations