

VALVOLINE™ V SPEED 4T SAE 20W-40 MOTORCYCLE OIL

Valvoline V Speed 4T SAE 20W-40 is a premium 4T oil specially formulated to provide year-round protection for 4-Stroke motorcycle engines. It is recommended for all standard motorcycles from leading brands for tough city riding conditions.

V SPEED 4T ADVANTAGES

- It meets the requirements of leading motorcycle manufacturers.
- Very good deposit control for cleaner engines - 4 Tech Chemistry technology.
- Strong oil film for perfect protection and lubrication with reduced wear under a wide temperature range.
- Higher viscosity for increased component life.

PERFORMANCE LEVEL
API SF

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	
SAE Viscosity Grade	20W-40
Kinematic Viscosity, cSt @ 100^{o}C	14.44
Kinematic Viscosity, cSt @ 40^{o}C	144.4
Viscosity Index	98
Density @ 30^{o}C, g/cm^{3}	0.8849
Flash Point, ^{o}C	266
TBN, mg KOH/g	5.6
CCS Viscosity @ -15^{o}C, cP	5721
Pour Point, ^{o}C	-9

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

	Effective Date	Author
Product Code: 250026	**Oct 2021**	**AUS**

™Trademark of Valvoline or its subsidiaries, registered in various countries ©2022 Valvoline